

# Specification

Linear lighting system

LR5535(B)




## LR5535(B)




### Features

- Several optional diffuser: general PC diffuser, flexible PC diffuser, flexible anti-glare diffuser, black diffuser, aluminium blind diffuser
- 50mm large luminous surface, rimless recessed design, integrated into architecture.
- Leakage proof shield design, perfect details.
- AL6063-T5 aluminum profile with high-quality surface treatment, black, white and silver are optional.
- Multiple optional connectors: 180 ° direct connection, L type, T type, X type



## Details



## Standard Configuration

Picture	Item	Parameter	Model
	①Profile	Profile weight: 2.55kg/2.5m Size: L2500*W93*H35mm Material: AL6063-T5 Surface processing: Anodizing	LR5535(B)
	②Cover	Type: Frosted diffuser Material: PC Light transmittance: 75% Size: L2500*W48.8*H5.6mm PC Feature: The diffuser will extend (shrink) 0.8mm/m when the temperature raises (drops) 10°C.	/
	③End cap	Size: L55*W35*H22mm	EC-LR5535(B)
	⑤Install screw	Size: M3.5*40mm	CL-01



## Optional Accessories

Picture	Item	Parameter	Model
	Flexible strip D8280-24V-34mm	Material: FPC,CCT:1900/2300/2700/3000/3500/4000/5000/6000K; CRI > 80/>95; Voltage: 24V; Power: 25W/m; Lumen: 3250Lm/m; Width: 34mm; Minimum cutting unit: 28LEDs/50mm;	D8280-24V-34mm
	Flexible strip D8560SWW-24V-34mm	Material: FPC, CCT : 2700-6000K; CRI > 80; Voltage: 24V; Power: 25W/m; Lumen: 2740Lm/m; Width: 34mm; Minimum cutting unit: 28LEDs/50mm; tunable white	D8560SWW-24V-34mm
	Rigid modular DY8280-24V-36mm	Material: FR4,CCT:1900/2300/2700/3000/3500/4000/5000/6000K; CRI > 80/>95; Voltage: 24V; Power: 25W/m; Lumen: 3250Lm/m; Width: 36mm; Minimum cutting unit: 28LEDs/50mm;	DY8280B-24V-36mm
	Rigid modular DY8560SWW-24V-36mm	Material: FR4, CCT : 2700-6000K; CRI > 80; Voltage: 24V; Power: 25W/m; Lumen: 2740Lm/m; Width: 36mm; Minimum cutting unit: 28LEDs/50mm; tunable white	DY8560SWW-24V-36mm
	Power supply (Non-dimming)	Size: L365*W30*H18mm Input voltage: AC220-240V; Frequency: 50-60Hz Output voltage: 24V; Max. current: 4.17A PF: ≥0.95; Efficiency: 0.91; Power: 100W Certification: CE/CB	BN-V24-100P-V1
	Power supply (DALI-dimming)	Size: L355*W30*H21mm Input voltage: AC200-240V; Frequency: 50-60Hz Output voltage: 24V; Max. current: 4.2A PF: ≥0.95; Efficiency: 0.90; Power: 100W Certification: TUV/CE/RCM	BK-DGV100-24V0D
	Power supply (1-10V-dimming)	Size: L355*W30*H21mm Input voltage: AC200-240V; Frequency: 50-60Hz Output voltage: 24V; Max. current: 4.2A PF: ≥0.95; Efficiency: 0.92; Power: 100W Certification: TUV/CE/RCM	BK-MGV100-24V0M
	Dimming solution accessory kit	Include 5PIN cable inside luminaire(3 of 18#, 2 of 22#, L=2600mm), 3 sets of male and female terminals.	CM-03
	Non-dimming solution accessory kit	Include 3PIN cable inside luminaire (3 of 18# cables, L=2600mm), 2 sets of male and female terminals.	CM-04



Picture	Item	Parameter	Model
	Non-dimming solution accessory kit	include 3PIN cable outside luminaire (3 of 18# cables, L=2600mm), 1 set of male and female terminals.	CM-05
	Dimming solution accessory kit	Include 5PIN cable outside luminaire (3 of 18#, 2 of 22#, L=2600mm), 2 sets of male and female terminals.	CM-06

## Cover type

Picture	Item	Parameter	Model
	②Cover	Type: Diffuse flexible mask Material: PC + silica gel Transparency: 70% Size: L50000*W48.7*H5.5mm	CV-LS5470FD(F)
		Type: Prismatic flexible mask Material: PC flexible/emboss Transparency: 60% Size: L50000*W48.7*H5.5mm	CV-LS5470FP(F)

## Corner fittings

EX-E1 (I-type 180°)	EX-E2 (L-type 90°)	EX-E3 (L-type 90°)	EX-E4 (T-type 90°)
			




EX-E5 (X-type 90°)	EX-E6 (L-type 120°)	EX-E7 (7-type 60°)	EX-E8 (L-type 120°)
			
EX-E9 (Y-type 120°)	EX-E10 (7-type 60°)	EX-E11 (X-type 60°+120°)	EX-E12 (T-type 60°+120°)
			
EX-17			
			


## Optical Parameter

D8280-24V-34mm light source, frosted diffuser

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




Flux out: 1334 lm




**Package**

Mode 1 :



Mode 2 :



Components	Packaging material	Size(mm)	NW(kg)	GW(kg)	Content
Single piece	Hat box	2560*113*61mm	2.52	3.02	1pcs/box
Whole bundle	Hat box	2580*256*207mm	15.3	18.3	6pcs/box
Whole box packaging	Paper box	2580*211*170mm	20.4	23.4	8pcs/box

