


Specification

Integrated Furniture Lighting

LS5050



LS5050




Features

DLS1.0, a special local auxiliary lighting system, can be widely used in various interior decoration scenarios and local light spaces. A touch of auxiliary decorative lighting in addition to the basic lighting creates different atmospheres and visual enjoyment.

Embellish life with light that follows you whenever you go.

- 1、 “Dots-free”lighting
Perfect homogenous lighting.
- 2、 Various diffuser options
Several options of diffusers, In various shapes and light distribution plans Complete with everything needed
- 3、 “Two” end caps
Two options of end cap for two ways of wire outgoing, Close-fitting design without screws makes installation much easier
- 4、 Various installation methods
A wide range of installation accessories wider applications
- 5、 “One” cut
Consistent length between diffuser and profile
- 6、 Smart control for unlimited possibilities
Perfectly match the profiles like customized, Control by hand sweep or touching



Details



Standard Configuration

Picture	Item	Parameter	Model
	①Profile	Material: AL6063-T5 Profile weight: 1.218kg/m Size: L2500*W50*H50mm Surface processing: Anodizing	/
	②Cover	Type: Frosted diffuser Material: PC Light transmittance: 85% Size: L2500*W44.7*H6.1mm (shrink) 0.8mm/m when the temperature rises (drops) 10°C.	/
	③End caps	Size: L50*W50*H12mm	EC-LS5050



Optional Accessories

Picture	Item	Parameter	Model
	Pendant-with junction box	Cord:D1.5*2000mm(D1.5*4000mm) Box:L80*W80*H30mm	PY-D
	Pendant-without junction box	Cord:D1.5*2000mm(D1.5*4000mm)	PN-D
	Pendant rod	Size:φ13.5*(500/1000)mm Other:0.5-1.0/1.0-2.0M adjustable	PG-I
	Splicing Bar	Material: AL6063-T5 Size: L400*W45.6*H21.4mm	EX-11
	Flexible strip D8280-24V-34mm	Material:FPC,CCT:1900/2300/2700/3000/3500/4000/5000/6000K; CRI > 80/90/95; Voltage: 24V; Power: 25W/m; Lumen: 3250Lm/m; Width: 34mm; Minimum cutting unit: 14LEDs/50mm;	D8280-24V-34mm

Package

Mode 1 :



Components	Packaging material	Size(mm)	NW(kg)	GW(kg)	Content
Single piece	Hat box	2580*67.5*75mm	3.5	4.65	1pcs/box
Whole bundle	Hat box	2580*202.5*150mm	18.0	27.9	6pcs/box

