

CSP DOT Series Specification



PD70RGBW

24V-12mm



【General description】

- Max.180° beam angle light-emitting
- Free connecting by soldering-free connectors
- High density LEDs, no shadow
- Ta: -40~60°C; Tc: 75°C (max)
- UL/UACK/CE/ROHS/REACH certification



【Dimension】

- | | |
|--|--|
| Input voltage: DC24V | Max.length: 5000mm(16.4') |
| CRI: / | Cutting unit: 100mm(3.93") |
| Max.power: 18.5W(1m) | LED pitch: / |
| Power range: 15.1~18.5W(1m) | Min. bend diameter: Φ 60mm(2.36") |
| Rated current: 0.7A(1m) | Mounting: 3M tape |
| Typical Power: 16.8W(1m) | Copper foil: 2oz |
| IP: IP20/IP65 | |
| On-off times: 10000 (test times) | |
| Warranty: 5 years indoors / 5 years outdoors | |

【Photo-electric Parameters】


CRI	Color	CCT	Lumen(lm/m)	Lumen(lm/ft)	lm/W	ErP 2019
/	RGBSW	RGB+2700K	640	195	38	/
/	RGBWW	RGB+3000K	655	199	39	/
/	RGBNW	RGB+4000K	640	195	38	/
/	RGBW	RGB+6500K	640	195	39	/

- 1.The tolerance of output data can be vary up to 10%.
- 2.the output data tested according to IES TM-30-15.
- 3.the output data is based on IP20/1mterter, data of 5m in only for reference.
- 4.IP protection process leads changes to size, CCT and luminous flux.

【Electronic & output data】


IP Process	Picture	Picture description	Size	optional CCT/color for finished product	lumen output rate
NO	 NO/IP20	No proof	12mm*1.7mm	RGB+2700K/3000K/4000K/6500K	100%
NA	 NANO/IP65	Nano-proof	12mm*1.8mm	RGB+2700K/3000K/4000K/6500K	98%
ES	 ET/IP67	Extrusion tube	14mm*4.8mm	RGB+2700K/3000K/4000K/6500K	88%
EF	 EF/IP67	Extrusion filling	16mm*4.8mm	RGB+2700K/3000K/4000K/6500K	86%

【Accessories Information】


Name	Picture	Code	coding	description
Fixed Clip		94-02-00-0004	FSW12SA	Silicone clip, screw: PA 3*8mm, suitable for 12mm FPC,EF/ET strip
Silicone Plug Kit		94-02-00-0048	DT12EA-A	Silicone plug kit, suitable for 12mm board width, ET/EF series silicone extrusion light strip
Silicone stopper kit		94-02-00-0049	DW12EA-A	Silicone tail plug kit, suitable for 12mm board width, ET/EF series silicone extrusion light strip
Mounting groove		94-02-00-0026	CPT12EA-16100100	Transparent PVC mounting groove, suitable for 12mm FPC, silicone extruded EF/ET strip
Stopper glue		94-16-03010001	AS-PG-0003	Silicone gel, suitable for ET/EF/EG/ERG waterproof LED strip

【Packing】

Colors brand package(NONA)



General customized package



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	5000*12*1.7	5	250	0.15	7.5	8.58	41*41*26
NA	5000*12*1.8	5	250	0.16	8	9.08	41*41*26

Remark: data with 10% tolerance

【Precautions】

- Please drive the led strip with 24VDC isolated power, and the ripple of the constant voltage source should be less than 5%.
- Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- Do not fold it in case any damage of LED beads.
- Do not pull the power wire hard to ensure the longevity. Any Crash may damage the LED light is prohibited.
- Please make sure the wire is connected to the anode and cathode correctly. The power output should be consistent with the voltage of the strip to avoid damage.
- LED lights should be stored in dry, sealed environment. Please only unpack it before usage. Ambient temperature: -25℃~40℃. Storage temperature: 0℃~60℃. Please use the strips without waterproof within indoor environment with humidity less than 70%.
- Please be careful during operation. Do not touch the AC power supply in case of electric shock.
- Please leave at least 20% power for the power supply during using to ensure there is enough power supply to drive the product.
- Do not use any acid or alkaline adhesives to fix the product (e.g.: glass cement).
- Do not scratch the product when IP process of the product is NA. Ultraviolet rays will damage the nano-layers on the product and seriously affect the life of the product.